Side mounted switches for high or low alarm duties (incl. gasket)

Nominal pressure	PN 16
Operating temperature	0 to 100°C
Ambient temperature	0 to 70°C
Density of the liquid	min. 0.7 kg/dm³
Operating differential	12 mm, fixed
Wetside material	Stainless steel (CrNiMo)
Flange material	Stainless steel (CrNiMo)
Housing material	seawater resistant die cast aluminium
Flange	square 82 x 82 mm, 63 mm PCD
Switch element	Microswitch SPDT with silver contacts
Switch rating	250 VAC, 3 A ... 30 VDC, 0.5 A
Enclosure	IP65
Weight	approx. 0.6 kg
Cable entry	M20 x 1.5
Safety Integrity Level (SIL)	SIL 1

Option: Type DC 01C 65	
Operating temperature	0 to 120°C
Enclosure	IP67

(All other technical data as type C 01C 65)

Flange dimensions

Connection diagram

Certificates
- Material certificates acc. to EN 10204-2.2 & EN 10204-3.1
- Test record: hydraulic pressure test and functional tests
- Test records of material tests: X-ray, ultrasonic, charpy, hardness etc.

Quality Assurance
- Bindle Ltd. is certified acc. to ISO 9001.

Lloyds Register of Shipping / LRS
- Type Approval Certificate No. 04/20005(E1)

Bindler AG | Ackerstrasse 42 | CH-8610 Uster | Switzerland
Phone +41 44 944 11 11 | info@bindler.ch | www.bindler.ch