

Series	Type	Material	Size	Viscosity	Operating Pressure	Operating Temperature	Page	
Economy Line 8	Visual 4	316316L	33.7 x 2.0	+ 150 cSt	max. flow @ 20°C	-45 ... 120°C	2	
	Visual 6						3	
	Visual 8	316316L	50.0 x 1.5	+ 800 cSt	max. flow @ 20°C	-45 ... 120°C	4	
	Visual 8						5	
	Pressure Temperature Rating for Economy Line 8							6
	PID diagram for control and flow alarm 1							7
	Pressure indicator							8
	Mounting specification for switches and capacitors, see 20010503							9

Information to the Economy program

If you do not find a solution for your application concerning pressure, temperature, connections or others, please have a look to our other VLI series: the Smart Line, Standard, Power, Pilot or Top of tank (www.wika.com) or contact your local Wika representative.

Standard delivery time for the Economy program is 6 to 10 working days, starting from receipt of technical and commercial confirmed order.

Delivery conditions according to "General conditions of contract for the supply of plant and machinery" VDM 2016.

Shipping approvals for:

ATEX, IV, DNV, GL, LRS, RINA, ABS/UL

can be downloaded under [www.wika.com > support > approvals \(type 3400 ... or 2014 ...\)](#)

Because of the NBR fuel being used for all Economy units it is not possible to fulfil the requirements of explosion proof equipment (ATEX/IECEx).

According to the assessment of PED (2014/68/EU) the VLI are classified to article 4.2, which means no CE marking and no material certificate 2.1 necessary.

For type (2014) please consult the diagram 2 on page no. 7 to determine maximum possible length of the unit.

Important note:

The complete economy line can only be ordered with the specifications mentioned in the data sheets. There are NO alterations and NO special executions possible!

Main parameters:

- Loose flange only
- NBR flange only
- Density 1.0 ... 1.1 (3400E); 0.8 ... 1.5 (2014E)
- Temperature -40°C ... +120°C
- Pilot (flow)@20°C