



Visual Level Indicators (VLI)

10/02

www.wika-eg.de

Standard Series

Series	Type	Material	Pipe Ø (D x L) (mm)	Operating Pressure	Operating Temperature	Scale
Standard 8	27814-A	316/316L	50.0 x 1.5	max. 16bar @ 20°C	-20°C ... +100°C	2
	27814-B	"	"	"	"	3
	27814-C	"	"	"	"	4
	27814-D	"	"	"	"	5
	Pressure-Temperature-Rating for Standard Series 8 Flange selection diagram for Standard Series 8					
Standard 20	34300-A	316L/316L	50.0 x 1.5	max. 20bar @ 20°C	-100°C ... +400°C	8
	34300-B	"	"	"	"	9
	34300-C	"	"	"	"	10
	34300-D	"	"	"	"	11
	Pressure-Temperature-Rating for Standard Series 20 Flange selection diagram for Standard Series 20					
Standard 50	50700-A	316/316L	54.0 x 2.0	max. 50bar @ 20°C	-20°C ... +400°C	14
	50700-B	"	"	"	"	15
	50700-C	"	"	"	"	16
	50700-D	"	"	"	"	17
	Pressure-Temperature-Rating for Standard Series 50 Flange selection diagram for Standard Series 50					
Mounting specification for sensors and transmitters showing on 200-200L						20