

Series	Type	Material	Pipe O.D. x s (mm)	Operating Pressure	Operating Temperature	Seite
<b>Standard 6</b>	23614-A	316/316L	53.0 x 1.5	max. 6bar @ 20°C	-80°C ... +150°C	<b>2</b>
"	23614-B	"	"	"	"	<b>3</b>
"	23614-K	"	"	"	"	<b>4</b>
"	23614-O	"	"	"	"	<b>5</b>
"	<a href="#">Pressure Temperature Rating for Standard Series 6</a>					<b>6</b>
"	<a href="#">Float selection diagram for Standard Series 6</a>					<b>7</b>
<b>Standard 28</b>	34300-A	316&316L	53.0 x 1.5	max. 28bar @ 20°C	-100°C ... +400°C	<b>8</b>
"	34300-B	"	"	"	"	<b>9</b>
"	34300-K	"	"	"	"	<b>10</b>
"	34300-O	"	"	"	"	<b>11</b>
"	<a href="#">Pressure Temperature Rating for Standard Series 28</a>					<b>12</b>
"	<a href="#">Float selection diagram for Standard Series 28</a>					<b>13</b>
<b>Standard 50</b>	32755-A	316/316L	54.0 x 2.0	max. 50bar @ 20°C	-80°C ... +400°C	<b>14</b>
"	32755-B	"	"	"	"	<b>15</b>
"	32755-K	"	"	"	"	<b>16</b>
"	32755-O	"	"	"	"	<b>17</b>
"	<a href="#">Pressure Temperature Rating for Standard Series 50</a>					<b>18</b>
"	<a href="#">Float selection diagram for Standard Series 50</a>					<b>19</b>
"	<a href="#">Mounting specification for switches and transmitters drawing no. 20010501</a>					<b>20</b>