KLAY-INSTRUMENTS

INSTRUCTION MANUAL PERAMIC

WARNING:

Before installing the "PERAMIC", read the warnings and advisements on page 4. For personal and system safety, and for optimum performance, make sure you thoroughly understand the contents before installing.

DESCRIPTION:

The PERAMIC is a solid state, *All Stainless*, pressure transmitter based on a ceramic pressure cell with a very high burst pressure. The amplifier system is based on a single Integrated Circuit, which ensures a perfect linearity in the 4-20 mA output. Also the transmitter is fully temperature compensated. The PERAMIC is made for pressure applications on liquids, gases and vapours. Zero and Span are internally adjustable in wide ranges.

A local digital indicator is available (option).




OPERATION PERAMIC:

The PERAMIC has no oil filling system, so the process pressure goes directly to the ceramic pressure cell. The voltage signal from the ceramic cell goes directly to the Integrated Circuit that converts this signal into 4-20 mA. Therefore the PERAMIC has a perfect linearity.

The PERAMIC is fully temperature compensated, which means that various process temperatures have <u>no</u> effect on the accuracy of the output signal.

DIMENSIONS PERAMIC (1/2" BSP acc. to DIN 16288):



PARTS DESCRIPTION:

MATERIAL:

1. Cover	SS 304
2. O-ring	EPDM
3. Venting	PA
 PG9 Cable Gland 	PA
Electronics Housing	SS 304
6. Foot	SS 316
Sensor (pressure cell)	Ceramic
8. Process connection 1/2" BSP (m)	SS 316
acc. to DIN 16288	

Note: The Sensor is sealed with an O-ring (VITON).

Other materials can be delivered on request.

BAROMETRIC REFERENCE:

The PERAMIC is in basic a so called "relative transmitter" which means that barometric changes will not affect the zero (4 mA). The venting nipple (3) is placed at the side of the electronic housing and is the barometric reference to atmospheric. The venting nipple must be kept clean.

H/E/PERAMIC/08-2016/14 Klay Instruments B.V. Page 1/4