

300 Series

Adjustable Power & Torque Reducer/Clutch

4.5 to 100 hp (3.3 to 75 kW)



Features

- Input: 1/2" shaft only
- 100% torque capacity
- No bearing
- Compact design
- Available in 10 sizes
- Wide range of configurations
- Low input speed
- 100% torque capacity
- 100% torque capacity
- 100% torque capacity

Applications

- Drives for material handling
- Drives for
- Drives for
- Drives for
- Drives for
- Drives for
- Drives for
- Drives for
- Drives for
- Drives for

Technical Data

Model	Input Power (hp)	Input Speed (rpm)	Output Speed (rpm)	Output Torque (lb-ft)
300-1	4.5	1725	1725	4.5
300-2	7.5	1725	1725	7.5
300-3	15	1725	1725	15
300-4	22.5	1725	1725	22.5
300-5	30	1725	1725	30
300-6	45	1725	1725	45
300-7	60	1725	1725	60
300-8	75	1725	1725	75
300-9	90	1725	1725	90
300-10	100	1725	1725	100

Key Features



Technical specifications and application details for the 300 Series Adjustable Power & Torque Reducer/Clutch. This section provides detailed information on the product's performance, dimensions, and usage. It includes a table of technical data and a list of key features. The text is partially obscured by a large watermark.

relief van