

PR-1 Series*

Adjustable Pressure Control Regulator



The PR-1 Series is a versatile specialty pressure reducing control regulator designed to fulfill a wide range of needs in instrumentation sample systems and other applications such as semiconductor processing gases. The many features of the PR-1 make it ideal for a wide range of applications controlling pressures at low to moderate flows in gas or liquid service. 316L material is used to facilitate welded connections. Stainless steel caps and adjusting screws prevent atmospheric corrosion and maintain appearance. Enhanced internal body surface finish of better than 25 Ra plus electropolishing allows easier cleaning and potentially less particle contamination in the flow stream.

Six different seat materials, three alternate orifice sizes and eight pressure control ranges with stainless diaphragms offer the user a wide spectrum of capabilities for pressure control with inlet pressures up to 6,000 psig and standard operating temperatures up to 500° F (260° C).

* Replaces the LPR and MR Series.

Features & Specifications

- Gas or liquid service
- 316L stainless steel, Inconel®, Teflon®, and Tefzel® only in flow stream
- Electropolished 316L body with better than 25 Ra diaphragm cavity surface finish
- Stainless steel cap with stainless steel adjusting screw
- Inlet pressures of up to 6,000 psi
- Adjustable outlet pressure ranges of 0–6 psig, 0–10 psig, 0–25 psig, 0–50 psig, 0–100 psig, 0–250 psig, 0–500 psig, and 0–750 psig
- Operating temperatures of –40° F to +500° F (–40° C to +260° C)
- 20µ filters
- Bubble-tight shutoff under most conditions
- Cv flow coefficient: 0.06

Options

- Wetted materials of construction: Monel®, Hastelloy® and titanium
- Diaphragm attached poppet
- Special fittings
- Diaphragm assist spring for vacuum purging
- Larger Cv's of 0.2 and 0.5, smaller Cv's of 0.025
- Panel mount (1 $\frac{3}{8}$ " mounting hole)

Maximum Temperature & Operating Inlet Pressures

Seat Material	Maximum Temperature*	@	Maximum Operating Inlet Pressure
Tefzel®	150° F (66° C)	@	3,600 psig (24.82 MPa)
High density Teflon®	150° F (66° C)	@	3,600 psig (24.82 MPa)
CF Teflon®	175° F (80° C)	@	3,600 psig (24.82 MPa)
PCTFE (formerly Kel-F® 81)	175° F (80° C)	@	6,000 psig (41.37 MPa)
Polyimide	500° F (260° C)	@	3,600 psig (24.82 MPa)
Polyimide	175° F (80° C)	@	6,000 psig (41.37 MPa)
PEEK™	500° F (260° C)	@	3,600 psig (24.82 MPa)
PEEK™	175° F (80° C)	@	6,000 psig (41.37 MPa)

* Temperatures in excess of 175° F (80° C) require the use of a metal knob or the tamper-proof option.

Circle Seal Controls

2301 Wardlow Circle • Corona, CA 92880
 Phone (951) 270-6200 • Fax (951) 270-6201
www.circle-seal.com

pressure regulators