Features

- Microprocessor-based
- 4-20mA analogue output
- Voltage-free relay contacts
- RS485 digital interface
- Alphanumeric dot-matrix display
- "One-Person" calibration
- Small size
- **Certified ATEX II 2 G Ex d IIC T6**
- Low power consumption
- Standalone operation

The Xenseo 5000, is a high-quality and compact, intelligent gas sensor that offers a host of sophisticated features to provide fast, reliable warnings against excessive concentrations of combustible gases.

The 5000 will operate as a stand-alone instrument or in conjunction with a control device or system. The 5000 is housed in an enclosure, comprises separate electronics and may be configured or calibrated by one person without disconnecting the hazard area wires. The gas concentration is output as an 4-20mA proportional signal, which also indicates instrument status. The 5000 is fully user programmable and no physical adjustments are necessary during calibration as the ambient computer stores the calibration procedure. All user variables are stored in non-volatile memory (EEPROM) and retained indefinitely even during mains power failure.

Typical Applications for the 5000:

- **Oil refineries**
- Chemical processing
- Offshore platforms
- Gas processing
- Oil and gas storage depots
- Gas pipelines
- Tank farms
- Laboratories
- Petrochemical industry

The 5000 consists of two modules, a control unit and a sensor unit, connected together by a four-core cable. The sensor unit contains the catalytic detector element in one arm of a Wheatstone bridge circuit. The resistance is amplified to give a voltage proportional to the gas concentration. This voltage is then processed by the CPU. A watchdog circuit monitors the correct operation of the CPU. If a failure is detected

The 5000 is calibrated in use (as opposed to laboratory) the magnetic wand as a keypad. The operator is then guided through a series of options in a user-friendly menu. The CPU constantly