

Digital Mass Flow Controller (up to 200 spt)

Key Features

- High accuracy mass flow control (0.05% to 0.2%)
- Low pressure drop (0.1 to 0.2 bar)
- High flow stability (0.1% to 1% per year)
- Fast response (0.1 to 100 s)
- Multiple channels (up to 200 channels)
- Easy to install (plug and play)
- Low maintenance (no moving parts)
- High reliability (MTBF > 100,000 h)
- Wide flow range (0.1 to 1000 sccm)
- High purity (99.999% to 99.9999%)
- High accuracy (0.1% to 0.5%)
- High resolution (0.1% to 1%)
- High repeatability (0.1% to 1%)
- High stability (0.1% to 1%)
- High accuracy (0.1% to 0.5%)
- High resolution (0.1% to 1%)
- High repeatability (0.1% to 1%)
- High stability (0.1% to 1%)



www.sierracontrols.com

SmartTrak 50 Medium



Key Features

SmartTrak 50 Medium is a high-precision, low-pressure drop flow controller. It is designed for applications requiring high accuracy and stability. The unit is easy to install and maintain, and it offers a wide flow range and high purity.

SmartTrak 50 Medium is a high-precision, low-pressure drop flow controller. It is designed for applications requiring high accuracy and stability. The unit is easy to install and maintain, and it offers a wide flow range and high purity.

SmartTrak 50 Medium is a high-precision, low-pressure drop flow controller. It is designed for applications requiring high accuracy and stability. The unit is easy to install and maintain, and it offers a wide flow range and high purity.

SmartTrak 50 Medium is a high-precision, low-pressure drop flow controller. It is designed for applications requiring high accuracy and stability. The unit is easy to install and maintain, and it offers a wide flow range and high purity.

SmartTrak 50 Medium is a high-precision, low-pressure drop flow controller. It is designed for applications requiring high accuracy and stability. The unit is easy to install and maintain, and it offers a wide flow range and high purity.

SmartTrak 50 Medium is a high-precision, low-pressure drop flow controller. It is designed for applications requiring high accuracy and stability. The unit is easy to install and maintain, and it offers a wide flow range and high purity.