

Inductive Conductivity Meter ILM

357065

Product Description

Accurate measurement of the conductivity of aqueous media
2000 µS/cm, 2000 µS/cm
Temperature compensation: automatic, manual and
programmable

Product Range

Conductivity of 0.1 µS/cm to 2000 µS/cm
Temperature compensation: 0, 25 and 50 °C
0.1 µS/cm to 2000 µS/cm

Operating Instructions

The ILM is a rugged, stainless steel inductive conductivity
probe suitable for use in a wide range of aqueous media
It is available in 2000 µS/cm or 2000 µS/cm
It is available in 2000 µS/cm or 2000 µS/cm
It is available in 2000 µS/cm or 2000 µS/cm
It is available in 2000 µS/cm or 2000 µS/cm
It is available in 2000 µS/cm or 2000 µS/cm

Specifications

Material: stainless steel
Temperature range: 0 to 100 °C
Accuracy: ±0.1%
Resolution: 0.1 µS/cm
Response time: 100 ms
Output: 4-20 mA
Power supply: 24V DC
Dimensions: 100 x 100 x 100 mm

Accessories

Stainless steel probe
Stainless steel probe
Stainless steel probe
Stainless steel probe
Stainless steel probe
Stainless steel probe

Accessories



Other ILM Models



Other ILM Models



Support and Service

